

Allgemeine Information

Technisch - Systeme

Ean	8021696191997
Artikel	FLUO WIDE 1200 3000K BK
Installation	Systeme
Garantie	5 years
Bruttogewicht	4.88 kg
Volumen	0.018311 m ³

Technische Information

Nettogewicht	2.89 kg
Isolationsklasse	I
Schutzindex	IP20
Einhaltung	CE
Betriebstemperatur	0° ~ +40 °C
Dimmer	NO, On-Off
Leistung	220-240 V AC 50/60 Hz
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic, tridonic
einschließlich Zubehör	Mounting kit (suspension, recessed, surface), Dimmable driver, Luminous corner, Structure connector

Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	Replaceable (by qualified operators only)
Leistung	27 W
Emissionen	Direct
Maximaler Verbrauch	max 27,00 W
Merkmale LED	LED SMD SAMSUNG
CCT LED	3000 K
Dauer LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Lichtstrahlwinkel	105°
Lichtstrahlfluss	3750 lm
Nützlicher Lichtstrom	2700 lm

