

Allgemeine Information

Technisch - Systeme

Ean	8021696192482
Artikel	FLUO WIDE 1200 4000K WH
Installation	Systeme
Garantie	5 years
Bruttogewicht	4.88 kg
Volumen	0.018311 m ³

Technische Information

Nettogewicht	2.89 kg
Isolationsklasse	I
Schutzindex	IP20
Einhaltung	CE
Betriebstemperatur	0° ~ +40 °C
Dimmer	NO, On-Off
Leistung	220-240 V AC 50/60 Hz
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic, tridonic
einschließlich Zubehör	Mounting kit (suspension, recessed, surface), Dimmable driver, Luminous corner, Structure connector

Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	Replaceable (by qualified operators only)
Leistung	27 W
Emissionen	Direct
Maximaler Verbrauch	max 27,00 W
Merkmale LED	LED SMD SAMSUNG
CCT LED	4000 K
Dauer LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Lichtstrahlwinkel	105°
Lichtstrahlfluss	4050 lm
Nützlicher Lichtstrom	2900 lm

