


Allgemeine Information

Innen - Wandleuchten



Ean	8021696306810
Artikel	KOMODO-2 AP BIANCO
Installation	Wandleuchten
Garantie	5 years
Bruttogewicht	0.83 kg
Volumen	0.006006 m ³

Technische Information



Nettogewicht	0.7 kg
Isolationsklasse	II
Schutzindex	IP20
Einhaltung	CE
Betriebstemperatur	0° ~ +40 °C
Dimmer	NO, On-Off
Leistung	220-240 V AC 50/60 Hz Integrated switch button Integrated USB socket
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic
Verstellbarkeit	vert. 0°-90°, orizz. 0°-180°

Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	Replaceable (by qualified operators only)
Leistung	4,5 W
Emissionen	Direct
Maximaler Verbrauch	max 4,50 W
Merkmale LED	LED SMD
CCT LED	3000 K
Dauer LED (t. 25°C)	20000 h
CRI	> 80
Lichtstrahlwinkel	25°
Lichtstrahlfluss	250 lm
Nützlicher Lichtstrom	210 lm
Photobiologisches Risiko	2
Standby-Leistung	< 0.50 W