


## Allgemeine Information

### Technisch - Systeme

<b>Ean</b>	8021696271217
<b>Artikel</b>	OFFICE SP 4000K WH
<b>Installation</b>	Systeme
<b>Garantie</b>	5 years
<b>Bruttogewicht</b>	1.86 kg
<b>Volumen</b>	0.004128 m <sup>3</sup>

## Technische Information

<b>Nettogewicht</b>	1.82 kg
<b>Isolationsklasse</b>	I
<b>Schutzindex</b>	IP20
<b>Einhaltung</b>	CE
<b>Betriebstemperatur</b>	0° ~ +40 °C
<b>Dimmer</b>	Non-dimmable, On-Off
<b>Leistung</b>	220-240 V AC 50/60 Hz
<b>Energieversorgung</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Lastwiderstand</b>	IK06



## Quellinfo

<b>Integrierte Quelle</b>	Integrated LED module
<b>Austauschbare Quelle</b>	Replaceable (by qualified operators only)
<b>Leistung</b>	30 W
<b>Emissionen</b>	Direct
<b>Maximaler Verbrauch</b>	max 30 W
<b>Merkmale LED</b>	LED SMD
<b>CCT LED</b>	4000 K
<b>Dauer LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 90
<b>SDCM</b>	3
<b>Lichtstrahlwinkel</b>	37°
<b>UGR Maximal</b>	< 16
<b>Lichtstrahlfluss</b>	3700 lm
<b>Nützlicher Lichtstrom</b>	2700 lm