


Allgemeine Information


Technisch - Systeme

Ean	8021696270180
Artikel	STEEL ACCENT 3000K WH
Installation	Systeme
Garantie	5 years
Bruttogewicht	2.52 kg
Volumen	0.017817 m ³



Technische Information

Nettogewicht	1.98 kg
Isolationsklasse	I
Schutzindex	IP20
Einhaltung	CE
Betriebstemperatur	0° ~ +40 °C
Dimmer	NO, On-Off
Leistung	220-240 V AC 50/60 Hz
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic, osram
einschließlich Zubehör	Mounting kit (suspension or surface), Straight continuous linear connector



Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	Replaceable (by qualified operators only)
Leistung	36 W
Emissionen	Direct + Indirect
Maximaler Verbrauch	max 36,00 W
Merkmale LED	LED SMD SAMSUNG
CCT LED	3000 K
Dauer LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Lichtstrahlwinkel	60+110°
UGR Maximal	< 16
Lichtstrahlfluss	4100 lm
Nützlicher Lichtstrom	3620 lm