

## Allgemeine Information


## Aussen - Strahler



Ean	8021696261287
Artikel	ULEX PR H15 SOURCE
Installation	Strahler
Garantie	5 years
Bruttogewicht	0.76 kg
Volumen	0.00252 m <sup>3</sup>

## Technische Information

Nettogewicht	0.66 kg
Isolationsklasse	I
Schutzindex	IP65
Einhaltung	CE
Betriebstemperatur	-15° ~ +45 °C
Dimmer	NO, On-Off
Leistung	220-240 V AC 50/60 Hz
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic
Lastwiderstand	IK06
Verstellbarkeit	vert. +30°/-10°
einschließlich Zubehör	Glare shielding cover, Base for external connection, Ground fixing spike



## Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	No
Leistung	8,5 W
Emissionen	Direct
Maximaler Verbrauch	max 8,50 W
Merkmale LED	LED SMD OSRAM
CCT LED	3000 K
Dauer LED (t. 25°C)	50000 h
CRI	> 80
Lichtstrahlwinkel	30°
Lichtstrahlfluss	640 lm
Nützlicher Lichtstrom	490 lm