

## Allgemeine Information


## Innen - Wandleuchten



|               |                                   |
|---------------|-----------------------------------|
| Ean           | 8021696361925                     |
| Artikel       | ZIG ZAG AP D33 ROUND OTTONE 3000K |
| Installation  | Wandleuchten                      |
| Garantie      | 5 years                           |
| Bruttogewicht | 0.62 kg                           |
| Volumen       | 0.002178 m³                       |

## Technische Information

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Nettogewicht       | 0.55 kg                                                                        |
| Isolationsklasse   | I                                                                              |
| Schutzindex        | IP20                                                                           |
| Einhaltung         | CE                                                                             |
| Betriebstemperatur | 0° ~ +40 °C                                                                    |
| Dimmer             | Non-dimmable, On-Off                                                           |
| Leistung           | 220-240 V AC 50/60 Hz                                                          |
| Energieversorgung  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Quellinfo

|                          |                       |
|--------------------------|-----------------------|
| Integrierte Quelle       | Integrated LED module |
| Austauschbare Quelle     | No                    |
| Leistung                 | 12,5 W                |
| Emissionen               | Indirect              |
| Maximaler Verbrauch      | max 12,5 W            |
| Merkmale LED             | LED SMD               |
| CCT LED                  | 3000 K                |
| Dauer LED (t. 25°C)      | 50000 h               |
| CRI                      | > 90                  |
| SDCM                     | 3                     |
| Lichtstrahlwinkel        | -                     |
| Lichtstrahlfluss         | 1300 lm               |
| Nützlicher Lichtstrom    | 1180 lm               |
| Photobiologisches Risiko | 1                     |