


## Allgemeine Information

## Innen - Wandleuchten



|                      |                             |
|----------------------|-----------------------------|
| <b>Ean</b>           | 8021696179308               |
| <b>Artikel</b>       | ZIG ZAG AP D53 3000K BIANCO |
| <b>Installation</b>  | Wandleuchten                |
| <b>Garantie</b>      | 5 years                     |
| <b>Bruttogewicht</b> | 0.69 kg                     |
| <b>Volumen</b>       | 0.002916 m <sup>3</sup>     |

## Technische Information



|                           |  |
|---------------------------|--|
| <b>Nettogewicht</b>       | 0.59 kg  |
| <b>Isolationsklasse</b>   | I  |
| <b>Schutzindex</b>        | IP20   |
| <b>Einhaltung</b>         | CE   |
| <b>Betriebstemperatur</b> | 0° ~ +40 °C  |
| <b>Dimmer</b>             | NO, On-Off   |
| <b>Leistung</b>           | 220-240 V AC 50/60 Hz  |
| <b>Energieversorgung</b>  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Quellinfo

|                                 |                       |
|---------------------------------|-----------------------|
| <b>Integrierte Quelle</b>       | Integrated LED module |
| <b>Austauschbare Quelle</b>     | No                    |
| <b>Leistung</b>                 | 23 W                  |
| <b>Emissionen</b>               | Indirect              |
| <b>Maximaler Verbrauch</b>      | max 23,00 W           |
| <b>Merkmale LED</b>             | LED SMD SAMSUNG       |
| <b>CCT LED</b>                  | 3000 K                |
| <b>Dauer LED (t. 25°C)</b>      | 50000 h               |
| <b>CRI</b>                      | > 80                  |
| <b>Lichtstrahlwinkel</b>        | -                     |
| <b>Lichtstrahlfluss</b>         | 2900 lm               |
| <b>Nützlicher Lichtstrom</b>    | 2600 lm               |
| <b>Photobiologisches Risiko</b> | 1                     |