



General info

Technical - Systems

| | |
|--------------|-------------------------|
| Ean | 8021696223032 |
| Item | ARCA WIDE 25W 4000K BK |
| Installation | Systems |
| Warranty | 5 years |
| Gross weight | 0.94 kg |
| Volume | 0.008678 m ³ |

Technical info

| | |
|--------------------------|---------------------------------------|
| Net weight | 0.7 kg |
| Insulation class | III |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 48 V DC |
| Power supply | Required, remoted, not included NO |
| Accessories not included | Arca profile |

Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 25 W |
| Emission | Direct |
| Max consupcion | max 25 W |
| Features LED | LED SMD SAMSUNG |
| CCT LED | 4000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 98° |
| Light beam flux | 3400 lm |
| Useful light flux | 2260 lm |
| Photobiological risk | 1 |