

General info


Technical - Recessed lights



| | |
|--------------|-------------------------|
| Ean | 8021696193519 |
| Item | BASIC FI WIDE 10W 3000K |
| Installation | Recessed lights |
| Warranty | 5 years |
| Gross weight | 0.45 kg |
| Volume | 0.00168 m³ |

Technical info

| | |
|--------------------------|---|
| Net weight | 0.37 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | Separate, included Replaceable (by qualified operators only), electronic, philips |
| Load resistance | IK06 |
| Front protection index | IP44 |
| Accessories not included | Dimmable driver |



Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 10 W |
| Emission | Direct |
| Max consupcion | max 10 W |
| Features LED | LED SMD |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 30000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 85° |
| Light beam flux | 1100 lm |
| Useful light flux | 870 lm |
| Photobiological risk | 1 |