



## General info

### Indoor - Wall lamps

|              |                                   |
|--------------|-----------------------------------|
| Ean          | 8021696364810                     |
| Item         | BEAN AP ROUND RECHARGEABLE NICKEL |
| Installation | Wall lamps                        |
| Warranty     | 5 years                           |
| Gross weight | 0.32 kg                           |
| Volume       | 0.00119 m <sup>3</sup>            |

## Technical info

|                       |                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------|
| Net weight            | 0.31 kg                                                                                   |
| Insulation class      | III                                                                                       |
| Protection index      | IP20                                                                                      |
| Compliance            | CE                                                                                        |
| Operating temperature | 0° ~ +40 °C                                                                               |
| Dimmer                | 1, Touch dimmer                                                                           |
| Power output          | 5 V DC 50/60 Hz                                                                           |
| Power supply          | Required, separate, not included (power charger, output 5 V DC 2 A USB-C type) electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | LED 3 W               |
| Emission               | Direct                |
| Max consupcion         | max 3 W               |
| Features LED           | LED SMD BRIDGELUX     |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 95                  |
| SDCM                   | 3                     |
| Light beam             | 27°                   |
| Light beam flux        | 200 lm                |
| Useful light flux      | 180 lm                |
| Photobiological risk   | 2                     |
| Standby power          | < 0.50 W              |