



## General info

### Indoor - Floor lamps

|              |                 |
|--------------|-----------------|
| Ean          | 8021696368665   |
| Item         | BLADE PT OTTONE |
| Installation | Floor lamps     |
| Warranty     | 5 years         |
| Gross weight | 8 kg            |
| Volume       | -               |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 5.8 kg                                                                         |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | 1, Dimmer on board                                                             |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | Separate, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | LED 15 W              |
| Emission               | Direct Asymmetrical   |
| Max consupcion         | max 15 W              |
| Features LED           | LED SMD               |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam flux        | 1900 lm               |
| Useful light flux      | 1300 lm               |
| Photobiological risk   | 1                     |
| Standby power          | < 0.50 W              |