



## General info

### Technical - Systems

|              |                            |
|--------------|----------------------------|
| Ean          | 8021696369976              |
| Item         | DEVA ACCENT 14W 4000K NERO |
| Installation | Systems                    |
| Warranty     | 5 years                    |
| Gross weight | 0.25 kg                    |
| Volume       | 0.00135 m <sup>3</sup>     |

## Technical info

|                          |                                 |
|--------------------------|---------------------------------|
| Net weight               | 0.23 kg                         |
| Insulation class         | III                             |
| Protection index         | IP20                            |
| Compliance               | CE                              |
| Operating temperature    | 0° ~ +40 °C [DO NOT COVER]      |
| Dimmer                   | Non-dimmable, On-Off            |
| Power output             | 24 V DC                         |
| Power supply             | Required, remoted, not included |
| Accessories not included | Deva profile                    |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 14 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 14 W                                  |
| Features LED           | LED SMD                                   |
| CCT LED                | 4000 K                                    |
| Duration LED (t. 25°C) | 30000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 34°                                       |
| Light beam flux        | 1600 lm                                   |
| Useful light flux      | 1290 lm                                   |
| Photobiological risk   | 1                                         |