ideal lux.





General info

Technical - Spotlights and Tracks

Ean	8021696283739
Item	DISPLAY WIDE D1125 4000K WH
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	1.13 kg
Volume	0.012444 m³

Technical info

Net weight	0.77 kg
Insulation class	Ш
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link 3-phase on-off profile

Source info

Integrated sourceIntegrated LED moduleRepleaceable sourceReplaceable (by qualified operators only)Power40 WEmissionDiffuseMax consuptionmax 40 WFeatures LEDLED SMD SAMSUNGCCT LED3000 hDuration LED (t. 25°c)50000 hSDCM3Light beam flux125°Light beam flux630 lmPhotobiological risk1		
Repleaceable sourceReplaceable (by qualified operators only)Power40 WEmissionDiffuseMax consuptionmax 40 WFeatures LEDLED SMD SAMSUNGCCT LED4000 KDuration LED (t. 25°c)50000 hCRI> 90SDCM3Light beam125°Light beam flux5800 lmUseful light flux3630 lm	• • • •	
Power40 WEmissionDiffuseMax consuptionmax 40 WFeatures LEDLED SMD SAMSUNGCCT LED4000 KDuration LED (t. 25°c)50000 hCRI> 90SDCM3Light beam125°Light beam flux5800 lmUseful light flux3630 lm	Integrated source	Integrated LED module
EmissionDiffuseMax consuptionmax 40 WFeatures LEDLED SMD SAMSUNGCCT LED4000 KDuration LED (t. 25°c)50000 hCRI> 90SDCM3Light beam125°Light beam flux5800 lmUseful light flux3630 lm	Repleaceable source	Replaceable (by qualified operators only)
Max consuptionmax 40 WFeatures LEDLED SMD SAMSUNGCCT LED4000 KDuration LED (t. 25°c)50000 hCRI> 90SDCM3Light beam125°Light beam flux5800 lmUseful light flux3630 lm	Power	40 W
Features LEDLED SMD SAMSUNGCCT LED4000 KDuration LED (t. 25°c)50000 hCRI> 90SDCM3Light beam125°Light beam flux5800 lmUseful light flux3630 lm	Emission	Diffuse
CCT LED 4000 K Duration LED (t. 25°c) 50000 h CRI > 90 SDCM 3 Light beam flux 5800 lm Useful light flux 3630 lm	Max consuption	max 40 W
Duration LED (t. 25°c) 50000 h CRI > 90 SDCM 3 Light beam 125° Light beam flux 5800 lm Useful light flux 3630 lm	Features LED	LED SMD SAMSUNG
CRI> 90SDCM3Light beam125°Light beam flux5800 lmUseful light flux3630 lm	CCT LED	4000 K
SDCM3Light beam125°Light beam flux5800 lmUseful light flux3630 lm	Duration LED (t. 25°c)	50000 h
Light beam125°Light beam flux5800 lmUseful light flux3630 lm	CRI	> 90
Light beam flux5800 lmUseful light flux3630 lm	SDCM	3
Useful light flux 3630 lm	Light beam	125°
-	Light beam flux	5800 lm
Photobiological risk 1	Useful light flux	3630 lm
	Photobiological risk	1

