

## General info


## Technical - Systems



|              |                                     |
|--------------|-------------------------------------|
| Ean          | 8021696303604                       |
| Item         | EGO TRACK DOUBLE 05W 3000K 1-10V BK |
| Installation | Systems                             |
| Guarantee    | 5 years                             |
| Gross weight | 0.28 kg                             |
| Volume       | 0.001555 m <sup>3</sup>             |

## Technical info

|                          |                                       |
|--------------------------|---------------------------------------|
| Net weight               | 0.21 kg                               |
| Insulation class         | III                                   |
| Protection index         | IP20                                  |
| Compliance               | CE                                    |
| Operating temperature    | 0° ~ +40 °C                           |
| Dimmer                   | 1, 1-10V                              |
| Power output             | 48 V DC                               |
| Power supply             | Required, remoted, not included<br>NO |
| Accessories not included | Honeycomb filters, Ego profile        |



## Source info

|                        |   |
|------------------------|---|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 5 W                                       |
| Emission               | Direct                                    |
| Max consumption        | max 5,00 W                                |
| Features LED           | LED SMD OSRAM                             |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3   |
| Light beam             | 30°                                       |
| Light beam flux        | 400 lm                                    |
| Useful light flux      | 360 lm                                    |
| Photobiological risk   | 1   |
| Standby power          | < 0.50 W                                  |