ideal lux.





General info

Technical - Systems

| Ean | 8021696286389 |
|--------------|------------------------------------|
| Item | EGO TRACK DOUBLE 24W 3000K DALI WH |
| Installation | Systems |
| Warranty | 5 years |
| Gross weight | 0.48 kg |
| Volume | 0.002657 m ³ |

Technical info

| Net weight | 0.33 kg |
|--------------------------|--|
| Insulation class | III |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | 1, DALI |
| Power output | 48 V DC |
| Power supply | Required, remoted, not included NO |
| Accessories not included | Narrow or Wide beam optics, Honeycomb filters, Ego profile |

190 190 190 190 40

| Source | | |
|--------|---|---|
| | - | ļ |
| | | 1 |

| Integrated source | Integrated LED module |
|------------------------|---|
| Repleaceable source | Replaceable (by qualified operators only) |
| Power | 24 W |
| Emission | Direct |
| Max consuption | max 24 W |
| Features LED | LED COB CITIZEN |
| CCT LED | 3000 K |
| Duration LED (t. 25°c) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 30° |
| Light beam flux | 2300 lm |
| Useful light flux | 1680 lm |
| Photobiological risk | 1 |
| Standby power | < 0.50 W |
| | |