

## General info


## Technical - Systems



|              |                                    |
|--------------|------------------------------------|
| Ean          | 8021696307589                      |
| Item         | EGO TRACK SINGLE 26W 3000K DALI BK |
| Installation | Systems                            |
| Warranty     | 5 years                            |
| Gross weight | 0.95 kg                            |
| Volume       | 0.003536 m³                        |

## Technical info

|                          |                                       |
|--------------------------|---------------------------------------|
| Net weight               | 0.8 kg                                |
| Insulation class         | III                                   |
| Protection index         | IP20                                  |
| Compliance               | CE                                    |
| Operating temperature    | 0° ~ +40 °C                           |
| Dimmer                   | 1, DALI                               |
| Power output             | 48 V DC                               |
| Power supply             | Required, remoted, not included<br>NO |
| Accessories not included | Ego profile                           |



## Source info

|                        |   |
|------------------------|---|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 26 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 26 W                                  |
| Features LED           | LED COB CITIZEN                           |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°c) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3   |
| Light beam             | 35°                                       |
| Light beam flux        | 3050 lm                                   |
| Useful light flux      | 2480 lm                                   |
| Photobiological risk   | 1   |
| Standby power          | < 0.50 W                                  |