



## General info

### Technical - Systems

|                     |                             |
|---------------------|-----------------------------|
| <b>Ean</b>          | 8021696303826               |
| <b>Item</b>         | EGO WIDE 26W 3000K 1-10V BK |
| <b>Installation</b> | Systems                     |
| <b>Guarantee</b>    | 5 years                     |
| <b>Gross weight</b> | 1.17 kg                     |
| <b>Volume</b>       | 0.004872 m <sup>3</sup>     |

## Technical info

|                                 |                                       |
|---------------------------------|---------------------------------------|
| <b>Net weight</b>               | 0.92 kg                               |
| <b>Insulation class</b>         | III                                   |
| <b>Protection index</b>         | IP20                                  |
| <b>Compliance</b>               | CE                                    |
| <b>Operating temperature</b>    | 0° ~ +40 °C                           |
| <b>Dimmer</b>                   | 1, 1-10V                              |
| <b>Power output</b>             | 48 V DC                               |
| <b>Power supply</b>             | Required, remoted, not included<br>NO |
| <b>Accessories not included</b> | Ego profile                           |

## Source info

|                               |   |
|-------------------------------|---|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | 26 W                                      |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 26,00 W                               |
| <b>Features LED</b>           | LED SMD SAMSUNG                           |
| <b>CCT LED</b>                | 3000 K                                    |
| <b>Duration LED (t. 25°C)</b> | 50000 h                                   |
| <b>CRI</b>                    | > 90                                      |
| <b>SDCM</b>                   | 3   |
| <b>Light beam</b>             | 110°                                      |
| <b>Light beam flux</b>        | 3400 lm                                   |
| <b>Useful light flux</b>      | 2750 lm                                   |
| <b>Photobiological risk</b>   | 1   |
| <b>Standby power</b>          | < 0.50 W                                  |