ideal lux.



212 522 0 62



General info

Technical - Spotlights and Tracks

Ean	8021696302980
Item	EOS TR 3-PHASE 15W 3000K DALI BK
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.75 kg
Volume	0.00378 m³

Technical info

Net weight	0.66 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, DALI
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link 3-phase 1-10V/DALI profile

Source info

Integrated source	Integra
Repleaceable source	Replac
Power	15 W
Emission	Direct
Max consuption	max 15
Features LED	LED C
CCT LED	3000 K
Duration LED (t. 25°c)	50000
CRI	> 90
SDCM	3
Light beam	20-55°
Light beam flux	1700 lr
Useful light flux	1300 lr
Photobiological risk	1
Standby power	< 0.50

Integrated LED module
Replaceable (by qualified operators only)
15 W
Direct
max 15 W
LED COB BRIDGELUX
3000 K
50000 h
> 90
3
20-55°
1700 lm
1300 lm
1
< 0.50 W