
ideal lux.



Fluo

General info

Technical - Systems

Ean	8021696192581
Item	FLUO ACCENT 1200 3000K BK
Installation	Systems
Guarantee	5 years
Gross weight	4.89 kg
Volume	0.018311 m³

Technical info

1205	50

Net weight	2.76 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Mounting kit (suspension, recessed, surface), Dimmable driver, Blinded corner, Structure connector

Source info

Integrated source	Integ
Repleaceable source	Repl
Power	30 W
Emission	Direc
Max consuption	max
Features LED	LED
CCT LED	3000
Duration LED (t. 25°c)	5000
CRI	> 80
SDCM	3
Light beam	30°
UGR Maximum	< 13
Light beam flux	2750
Useful light flux	2200

Integrated LED module	
Replaceable (by qualified operators only)	
30 W	
Direct	
max 30,00 W	
LED SMD OSRAM	
3000 K	
50000 h	
> 80	
3	
30°	
< 13	
2750 lm	
2200 lm	