

General info

Technical - Systems

| | |
|--------------|---------------------------|
| Ean | 8021696192420 |
| Item | FLUO ACCENT 1800 4000K BK |
| Installation | Systems |
| Guarantee | 5 years |
| Gross weight | 6.83 kg |
| Volume | 0.025675 m ³ |

Technical info

| | |
|--------------------------|--|
| Net weight | 3.86 kg |
| Insulation class | I |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic, tridonic |
| Accessories not included | Mounting kit (suspension, recessed, surface), Dimmable driver, Blinded corner, Structure connector |

Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 30 W |
| Emission | Direct |
| Max consumption | max 30,00 W |
| Features LED | LED SMD OSRAM |
| CCT LED | 4000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 80 |
| SDCM | 3 |
| Light beam | 30° |
| UGR Maximum | < 13 |
| Light beam flux | 2900 lm |
| Useful light flux | 2350 lm |

