



## General info

### Technical - Systems

|              |                         |
|--------------|-------------------------|
| Ean          | 8021696191997           |
| Item         | FLUO WIDE 1200 3000K BK |
| Installation | Systems                 |
| Warranty     | 5 years                 |
| Gross weight | 4.88 kg                 |
| Volume       | 0.02064 m³              |

## Technical info

|                          |   |
|--------------------------|---|
| Net weight               | 2.89 kg   |
| Insulation class         | I   |
| Protection index         | IP20  |
| Compliance               | CE  |
| Operating temperature    | 0° ~ +40 °C   |
| Dimmer                   | Non-dimmable, On-Off  |
| Power output             | 220-240 V AC 50/60 Hz   |
| Power supply             | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic                  |
| Accessories not included | Mounting kit (suspension, recessed, surface),<br>Dimmable driver, Luminous corner, Structure<br>connector |



## Source info

|                        |   |
|------------------------|---|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 27 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 27 W                                  |
| Features LED           | LED SMD SAMSUNG                           |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3   |
| Light beam             | 105°                                      |
| Light beam flux        | 3250 lm                                   |
| Useful light flux      | 2430 lm                                   |
| Photobiological risk   | 1   |