



## General info

### Indoor - Ceiling lamps

|                     |                         |
|---------------------|-------------------------|
| <b>Ean</b>          | 8021696270326           |
| <b>Item</b>         | FLY PL D90 3000K BIANCO |
| <b>Installation</b> | Ceiling lamps           |
| <b>Guarantee</b>    | 5 years                 |
| <b>Gross weight</b> | 17.22 kg                |
| <b>Volume</b>       | 0.09025 m <sup>3</sup>  |

## Technical info

|                                 |                                                                                          |
|---------------------------------|------------------------------------------------------------------------------------------|
| <b>Net weight</b>               | 11.09 kg                                                                                 |
| <b>Insulation class</b>         | I                                                                                        |
| <b>Protection index</b>         | IP40                                                                                     |
| <b>Compliance</b>               | CE                                                                                       |
| <b>Operating temperature</b>    | 0° ~ +40 °C                                                                              |
| <b>Dimmer</b>                   | NO, On-Off                                                                               |
| <b>Power output</b>             | 220-240 V AC 50/60 Hz                                                                    |
| <b>Power supply</b>             | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic |
| <b>Accessories not included</b> | Dimmable driver, upright module                                                          |

## Source info

|                               |                                           |
|-------------------------------|-------------------------------------------|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | 65 W                                      |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 65,00 W                               |
| <b>Features LED</b>           | LED SMD SAMSUNG                           |
| <b>CCT LED</b>                | 3000 K                                    |
| <b>Duration LED (t. 25°C)</b> | 50000 h                                   |
| <b>CRI</b>                    | > 80                                      |
| <b>SDCM</b>                   | 3                                         |
| <b>Light beam</b>             | 87°                                       |
| <b>UGR Maximum</b>            | < 19                                      |
| <b>Light beam flux</b>        | 9400 lm                                   |
| <b>Useful light flux</b>      | 7490 lm                                   |
| <b>Photobiological risk</b>   | 1                                         |