
ideal lux.





Fox

General info

Technical - Spotlights and Tracks

Ean	8021696302546
Item	FOX TR 3-PHASE 08W CRI90 3000K 1-10V WH
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.55 kg
Volume	0.00288 m ³

Technical info

Net weight	0.46 kg
Insulation class	П
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, 1-10V
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link 3-phase 1-10V/DALI profile

Source info

Integrated source	Integrat
Repleaceable source	Replace
Power	8 W
Emission	Direct
Max consuption	max 8 \
Features LED	LED CO
CCT LED	3000 K
Duration LED (t. 25°c)	50000 ł
CRI	> 90
SDCM	3
Light beam	41°
Light beam flux	1000 lm
Useful light flux	720 lm
Photobiological risk	1
Standby power	< 0.50

Integrated LED module
Replaceable (by qualified operators only)
8 W
Direct
max 8 W
LED COB BRIDGELUX
3000 K
50000 h
> 90
3
41°
1000 lm
720 lm
1
< 0.50 W