ideal lux.



Fox

General info

Technical - Spotlights and Tracks

Ean	8021696302553
Item	FOX TR 3-PHASE 15W CRI90 3000K 1-10V BK
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.68 kg
Volume	0.0042 m³

Technical info

Net weight	0.56 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, 1-10V
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link 3-phase 1-10V/DALI profile

Source info

Integrated source	Integrate
Repleaceable source	Replace
Power	15 W
Emission	Direct
Max consuption	max 15
Features LED	LED CC
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	41°
Light beam flux	1600 lm
Useful light flux	1350 lm
Photobiological risk	1
Standby power	< 0.50

Integrated LED module
Replaceable (by qualified operators only)
15 W
Direct
max 15 W
LED COB BRIDGELUX
3000 K
50000 h
> 90
3
41°
1600 lm
1350 lm
1
< 0.50 W

