
ideal lux.







General info

Technical - Spotlights and Tracks

Ean	8021696302591
Item	FOX TR 3-PHASE 25W CRI90 3000K 1-10V BK
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.81 kg
Volume	0.004995 m³

Technical info

Net weight	0.71 kg
Insulation class	П
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, 1-10V
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link 3-phase 1-10V/DALI profile

Source info

Integrated source	Integra
Repleaceable source	Replace
Power	25 W
Emission	Direct
Max consuption	max 25
Features LED	LED CO
CCT LED	3000 K
Duration LED (t. 25°c)	50000 H
CRI	> 90
SDCM	3
Light beam	35°
Light beam flux	2900 In
Useful light flux	2160 In
Photobiological risk	1
Standby power	< 0.50

Integrated LED module
Replaceable (by qualified operators only)
25 W
Direct
max 25 W
LED COB BRIDGELUX
3000 K
50000 h
> 90
3
35°
2900 lm
2160 lm
1
< 0.50 W