ideal lux.



Fox

General info

Technical - Spotlights and Tracks

Ean	8021696340852
Item	FOX TR 3-PHASE 08W CRI90 4000K 1-10V BK
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.55 kg
Volume	0.00264 m³

Technical info

Net weight	0.5 kg
Insulation class	Ш
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, 1-10V
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link 3-phase 1-10V/DALI profile

Source info

Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	8 W
Emission	Direct
Max consuption	max 8 W
Features LED	LED COB BRIDGELUX
CCT LED	4000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	41°
Light beam flux	1050 lm
Useful light flux	760 lm
Photobiological risk	1
Standby power	< 0.50 W

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 Fax +39 041 8872349 E-mail info@ideal-lux.com
www.ideal-lux.com

