



## General info

### Indoor - Ceiling lamps

|              |                                    |
|--------------|------------------------------------|
| Ean          | 8021696372082                      |
| Item         | GEMINI PL D061 ON-OFF OTTONE 4000K |
| Installation | Ceiling lamps                      |
| Warranty     | 5 years                            |
| Gross weight | 6.34 kg                            |
| Volume       | 0.0507 m <sup>3</sup>              |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 4.69 kg                                                                        |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 30 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 30 W                                  |
| Features LED           | LED SMD LUMILEDS                          |
| CCT LED                | 4000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 130°                                      |
| Light beam flux        | 3550 lm                                   |
| Useful light flux      | 2340 lm                                   |
| Photobiological risk   | 2                                         |