ideal lux.



Hotel

General info

Indoor - Wall lamps

| Ean | 8021696215709 |
|--------------|---------------------|
| Item | HOTEL AP2 ALL BLACK |
| Installation | Wall lamps |
| Warranty | 5 years |
| Gross weight | 2.02 kg |
| Volume | 0.01491 m³ |

Technical info

| 175 | 9 | 225 S |
|-----|-----|-------|
| | 320 | Y |

| Net weight | 1.41 kg |
|-----------------------|--|
| Insulation class | I |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 100-240 V AC 50/60 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), |
| | electronic |

Source info

| | modulo |
|------------------------|---------------------|
| Repleaceable source | Replaceable (LED: b |
| Power | E27/LED max 1 x 60 |
| Emission | Diffuse + Direct |
| Max consuption | max 60W / LED 1.5 |
| Features LED | LED SMD BRIDGEL |
| CCT LED | 3000 K |
| Duration LED (t. 25°c) | 20000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 23° |
| Light beam flux | 50 lm |
| Useful light flux | 40 lm |
| Photobiological risk | 2 |
| Recommended bulb | 123899 E27 GOCCI/ |

| Light bulb (not included), Integrated LED module |
|--|
| Replaceable (LED: by qualified operators only) |
| E27/LED max 1 x 60W / 1.5 W |
| Diffuse + Direct |
| max 60W / LED 1.5 W |
| LED SMD BRIDGELUX |
| 3000 K |
| 20000 h |
| > 90 |
| 3 |
| 23° |
| 50 lm |
| 40 lm |
| 2 |
| 123899 E27 GOCCIA 08W 3000K CRI80 BIANCO |