


General info

Indoor - Wall lamps



| | |
|--------------|-------------------------|
| Ean | 8021696291796 |
| Item | KOMODO-1 AP NERO |
| Installation | Wall lamps |
| Guarantee | 5 years |
| Gross weight | 0.98 kg |
| Volume | 0.006006 m ³ |

Technical info



| | |
|-----------------------|--|
| Net weight | 0.7 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50/60 Hz Integrated switch button Integrated USB socket |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic |
| Adjustability | vert. 0°-90°, orizz. 0°-180° |

Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 4,5 W |
| Emission | Direct |
| Max consumption | max 4,50 W |
| Features LED | LED SMD |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 20000 h |
| CRI | > 80 |
| Light beam | 25° |
| Light beam flux | 250 lm |
| Useful light flux | 210 lm |
| Photobiological risk | 2 |
| Standby power | < 0.50 W |