

## General info


## Outdoor - Recessed lights



|              |                            |
|--------------|----------------------------|
| Ean          | 8021696222837              |
| Item         | ROCKET FI D55 DOUBLE 4000K |
| Installation | Recessed lights            |
| Warranty     | 5 years                    |
| Gross weight | 0.4 kg                     |
| Volume       | 0.000819 m³                |

## Technical info

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| Net weight               | 0.31 kg                                           |
| Insulation class         | III                                               |
| Protection index         | IP67                                              |
| Compliance               | CE                                                |
| Operating temperature    | -15° ~ +45 °C                                     |
| Dimmer                   | Non-dimmable, On-Off                              |
| Power output             | 24 V DC                                           |
| Power supply             | Required, remoted, not included<br>NO, electronic |
| Load resistance          | IK07                                              |
| Accessories not included | Remote on-off driver                              |



## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | 2 W                   |
| Emission               | Direct                |
| Max consupcion         | max 2 W               |
| Features LED           | LED SMD OSRAM         |
| CCT LED                | 4000 K                |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam             | -                     |
| Light beam flux        | 160 lm                |
| Useful light flux      | 15 lm                 |
| Photobiological risk   | 1                     |