
ideal lux.





Smile

General info

Technical - Spotlights and Tracks

Ean	8021696189857
Item	SMILE TR 3-PHASE 20W CRI80 36° 4000K WH
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.87 kg
Volume	0.005011 m³

Technical info

Net weight	0.87 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Load resistance	IK06
Accessories not included	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

Source info

Integrated source	Inte
Repleaceable source	Rep
Power	20
Emission	Dire
Max consuption	ma
Features LED	LEI
CCT LED	400
Duration LED (t. 25°c)	500
CRI	> 8
SDCM	3
Light beam	36°
Light beam flux	315
Useful light flux	274

Integrated LED module Replaceable (by qualified operators only) 20 W Direct max 20 W LED COB PHILIPS 4000 K 50000 h > 80 3 36° 3150 lm 2740 lm