
# ideal lux.





## Smile

### General info

#### **Technical - Spotlights and Tracks**

Ean	8021696189994
Item	SMILE TR 3-PHASE 20W CRI80 50° 3000K WH
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.87 kg
Volume	0.005011 m³

#### **Technical info**

Net weight	0.87 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Load resistance	IK06
Accessories not included	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

#### Source info

Integrated source	Inte
Repleaceable source	Re
Power	20
Emission	Dir
Max consuption	ma
Features LED	LE
CCT LED	300
Duration LED (t. 25°c)	50
CRI	> 8
SDCM	3
Light beam	50
Light beam flux	30
Useful light flux	24

Integrated LED module Replaceable (by qualified operators only) 20 W Direct max 20 W LED COB PHILIPS 3000 K 50000 h > 80 3 50° 3000 lm 2490 lm