


Smile

General info

Technical - Spotlights and Tracks







Ean 8021696190099

Item SMILE TR 3-PHASE 30W CRI90 50° 3000K

WH

Installation Spotlights and Tracks

 $\begin{tabular}{lll} Warranty & 5 years \\ Gross weight & 0.87 kg \\ Volume & 0.005011 m^3 \end{tabular}$

Technical info

Net weight0.87 kgInsulation classIIProtection indexIP20ComplianceCE

Operating temperature $0^{\circ} \sim +40 {\,}^{\circ}\text{C}$

DimmerNon-dimmable, On-OffPower output220-240 V AC 50/60 Hz

Power supply In-built, included

Replaceable (by qualified operators only),

electronic, tridonic

Load resistance IK06

Accessories not included Honeycomb or Elliptical filter, White decorative

ring, Single connection on-off, Link on-off profile

Source info

Integrated source Integrated LED module

Repleaceable source Replaceable (by qualified operators only)

Power 30 W
Emission Direct
Max consuption max 30 W

Features LED COB PHILIPS

 CCT LED
 3000 K

 Duration LED (t. 25°c)
 50000 h

 CRI
 > 90

 SDCM
 3

 Light beam
 50°

 Light beam flux
 3500 lm

 Useful light flux
 2900 lm