

General info


Outdoor - Recessed lights



| | |
|---------------------|-----------------------------|
| Ean | 8021696325651 |
| Item | TAURUS PT D13 ACCENT SQUARE |
| Installation | Recessed lights |
| Guarantee | 5 years |
| Gross weight | 1.7 kg |
| Volume | - |

Technical info

| | |
|--------------------------------|--|
| Net weight | 1.7 kg |
| Insulation class | I |
| Protection index | IP67 |
| Compliance | CE |
| Operating temperature | -15° ~ +45 °C |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic |
| Recessed specifications | Ø 128 - h. ≥ 110 , 5-30 |
| Adjustability | vert. +/-30° |



Source info

| | |
|-------------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 11 W |
| Emission | Direct |
| Max consumption | max 11,00 W |
| Features LED | LED SMD OSRAM |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 80 |
| Light beam | 28° |
| Light beam flux | 840 lm |
| Useful light flux | 740 lm |