


**General info****Indoor - Ceiling lamps**

|                     |                               |
|---------------------|-------------------------------|
| <b>Ean</b>          | 8021696138640                 |
| <b>Item</b>         | UNIVERSAL PL D22 SQUARE 3000K |
| <b>Installation</b> | Ceiling lamps                 |
| <b>Warranty</b>     | 5 years                       |
| <b>Gross weight</b> | 0.82 kg                       |
| <b>Volume</b>       | 0.002432 m³                   |

**Technical info**

|                              |                                                                                |
|------------------------------|--------------------------------------------------------------------------------|
| <b>Net weight</b>            | 0.71 kg                                                                        |
| <b>Insulation class</b>      | II                                                                             |
| <b>Protection index</b>      | IP20                                                                           |
| <b>Compliance</b>            | CE                                                                             |
| <b>Operating temperature</b> | 0° ~ +40 °C                                                                    |
| <b>Dimmer</b>                | Non-dimmable, On-Off                                                           |
| <b>Power output</b>          | 220-240 V AC 50/60 Hz                                                          |
| <b>Power supply</b>          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

**Source info**

|                               |                       |
|-------------------------------|-----------------------|
| <b>Integrated source</b>      | Integrated LED module |
| <b>Replaceable source</b>     | No                    |
| <b>Power</b>                  | 17 W                  |
| <b>Emission</b>               | Direct                |
| <b>Max consupcion</b>         | max 17 W              |
| <b>Features LED</b>           | LED SMD               |
| <b>CCT LED</b>                | 3000 K                |
| <b>Duration LED (t. 25°C)</b> | 30000 h               |
| <b>CRI</b>                    | > 90                  |
| <b>SDCM</b>                   | 3                     |
| <b>Light beam</b>             | 110°                  |
| <b>Light beam flux</b>        | 2050 lm               |
| <b>Useful light flux</b>      | 1560 lm               |
| <b>Photobiological risk</b>   | 1                     |