

## General info


## Indoor - Wall lamps



|              |                                   |
|--------------|-----------------------------------|
| Ean          | 8021696369570                     |
| Item         | ZIG ZAG AP D76 ROUND OTTONE 3000K |
| Installation | Wall lamps                        |
| Warranty     | 5 years                           |
| Gross weight | 1.12 kg                           |
| Volume       | 0.004693 m³                       |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.99 kg                                                                        |
| Insulation class      | I                                                                              |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | 30 W                  |
| Emission               | Indirect              |
| Max consupcion         | max 30 W              |
| Features LED           | LED SMD               |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam             | -                     |
| Light beam flux        | 3100 lm               |
| Useful light flux      | 2810 lm               |
| Photobiological risk   | 1                     |