

**Info generali****Interno - Applique**

Indoor wall mounted adjustable lamp with multiple sources, in-built switch, in-built USB port and diffuse and direct light emission



|                      |                  |
|----------------------|------------------|
| <b>Ean</b>           | 8021696174822    |
| <b>Articolo</b>      | BOOK-2 AP BIANCO |
| <b>Installazione</b> | Applique         |
| <b>Garanzia</b>      | 5 years          |
| <b>Peso lordo</b>    | 2 kg             |
| <b>Volume</b>        | 0.012763 m³      |

**Info tecniche e installative**

|                                |                                                                                |
|--------------------------------|--------------------------------------------------------------------------------|
| <b>Peso netto</b>              | 1.57 kg                                                                        |
| <b>Classe di isolamento</b>    | I                                                                              |
| <b>Grado di protezione</b>     | IP20                                                                           |
| <b>Conformità</b>              | CE                                                                             |
| <b>Temperatura d'esercizio</b> | 0° ~ +40 °C                                                                    |
| <b>Dimmer</b>                  | Non-dimmable, On-Off                                                           |
| <b>Alimentazione</b>           | 220-240 V AC 50/60 Hz                                                          |
| <b>Alimentatore</b>            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

**Info sorgente e prestazionali**

|                              |                                                  |
|------------------------------|--------------------------------------------------|
| <b>Sorgente integrata</b>    | Light bulb (not included), Integrated LED module |
| <b>Sorgente sostituibile</b> | Replaceable (LED: by qualified operators only)   |
| <b>Potenza</b>               | G9/LED max 1 x 28W / 3 W                         |
| <b>Emissione</b>             | Diffuse + Direct                                 |
| <b>Consumo massimo</b>       | max 28W / LED 3.0 W                              |
| <b>Caratteristiche LED</b>   | LED SMD                                          |
| <b>CCT LED</b>               | 3000 K                                           |
| <b>Durata LED (t. 25°c)</b>  | 15000 h                                          |
| <b>CRI</b>                   | > 90                                             |
| <b>SDCM</b>                  | 3                                                |
| <b>Flusso sorgente</b>       | 190 lm                                           |
| <b>Flusso utile</b>          | LED 170 lm                                       |
| <b>Rischio fotobiologico</b> | 2                                                |
| <b>Lampadina consigliata</b> | 305486 G9 4.0W 3000K CRI80                       |