

Info generali

Interno - Applique


Indoor wall mounted adjustable lamp with multiple sources, in-built switch, in-built USB port and diffuse and direct light emission



Ean	8021696259833
Articolo	SET UP MAP2 NICKEL
Installazione	Applique
Garanzia	5 years
Peso lordo	1.15 kg
Volume	0.006292 m³

Info tecniche e installative

Peso netto	0.9 kg
Classe di isolamento	I
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic
Accessori non inclusi	Lampshade



Info sorgente e prestazionali

Sorgente integrata	Light bulb (not included), Integrated LED module
Sorgente sostituibile	Replaceable (LED: by qualified operators only)
Potenza	max 1 x 42W / 3 W
Emissione	Diffuse + Direct
Consumo massimo	max 42W / LED 3 W
Caratteristiche LED	LED SMD
CCT LED	3000 K
Durata LED (t. 25°C)	20000 h
CRI	> 90
SDCM	3
Fascio luminoso	25°
Flusso sorgente	200 lm
Flusso utile	LED 130 lm
Rischio fotobiologico	2