



## Info generali

### Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

<b>Ean</b>	8021696189895
<b>Articolo</b>	SMILE TR 3-PHASE 30W CRI80 36° 4000K WH
<b>Installazione</b>	Proiettori e Binari
<b>Garanzia</b>	5 years
<b>Peso lordo</b>	0.87 kg
<b>Volume</b>	0.005011 m <sup>3</sup>

## Info tecniche e installative

<b>Peso netto</b>	0.87 kg
<b>Classe di isolamento</b>	II
<b>Grado di protezione</b>	IP20
<b>Conformità</b>	CE
<b>Temperatura d'esercizio</b>	0° ~ +40 °C
<b>Dimmer</b>	Non-dimmable, On-Off
<b>Alimentazione</b>	220-240 V AC 50/60 Hz
<b>Alimentatore</b>	In-built, included Replaceable (by qualified operators only), electronic, tridonic
<b>Resistenza al carico</b>	IK06
<b>Accessori non inclusi</b>	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

## Info sorgente e prestazionali

<b>Sorgente integrata</b>	Integrated LED module
<b>Sorgente sostituibile</b>	Replaceable (by qualified operators only)
<b>Potenza</b>	30 W
<b>Emissione</b>	Direct
<b>Consumo massimo</b>	max 30 W
<b>Caratteristiche LED</b>	LED COB PHILIPS
<b>CCT LED</b>	4000 K
<b>Durata LED (t. 25°c)</b>	50000 h
<b>CRI</b>	> 80
<b>SDCM</b>	3
<b>Fascio luminoso</b>	36°
<b>Flusso sorgente</b>	4200 lm
<b>Flusso utile</b>	3650 lm